

Go Power![®]

250AH 12V LITHIUM BATTERY



EFFICIENT HIGH-PERFORMANCE SOLAR POWER STORAGE



MODEL #: GP-LiFePO4-250

Features:

- Compatible with all Go Power! solar, inverters and charge controllers
- Max Power Capacity; carries almost double the power of regular batteries
- Lightweight
- Quick charging
- Over and under voltage protection
- Over and under temperature protection
- Charge and discharge over current protection
- Short circuit protection
- 2-year warranty

Only suitable for 12-volt applications.

DO NOT WIRE IN SERIES.

SPECIFICATIONS

Technology	Lithium Iron Phosphate
Nominal Voltage	12.8 V
Nominal Capacity	250 Ah
Nominal Operating Temperature	77 ±5 °F (25 ±3 °C)
Maximum Charge Voltage	14.6 VAC
Maximum Discharge Current	100A (continuous); 120A (30 minutes); 200A (5 seconds)
Over-charge Protection Voltage	14.6V
Over-charge Protection Voltage of a single cell	2.1V
Maximum Charge Temperature Range	32°F (0°C) - 131°F (55°C)
Maximum Discharge Temperature Range	-4°F (-20°C) to 131°F (55°C)
BMS Leakage Current	≤3mA
Certifications	UN 38.3; CE
Cycle Life	80% Depth of Discharge ~ 3000 cycles

MECHANICAL

Length	20.5 in / 520 mm
Width	9.5 in / 240 mm
Height	8.8 in / 223 mm
Weight	80 lbs / 36 kg
Carrying	Nylon Straps

MATERIALS

Case and Cover	ABS
Active	LiFePO4
Venting Valve	Rubber, opening pressure 8-20kPa

Specifications may be subject to change. Product may not be exactly as shown.
Specifications subject to local environmental conditions.



250AH 12V LITHIUM BATTERY

Unit Dimensions:



PLEASE NOTE

Lithium batteries ship under Class 9 Dangerous Goods PI 965 Section IA, which requires special carrier instructions. Please contact your carrier company to determine their requirements for shipping.

MSDS Sheets are available upon request.